




LAYERING Potter's Choice

Celadon


Cone 5/6




PC-4 Palladium over C-25 Downpour



PC-20 Blue Rutile over C-25 Downpour





PC-21 Arctic Blue over C-25 Downpour




PC-25 Textured Turquoise over C-25 Downpour



PC-27 Tourmaline over C-25 Downpour



PC-28 Frosted Turquoise over C-25 Downpour




PC-30 Temmoku over C-25 Downpour




Conforms to
ASTM D-4236

PC-32 Albany Slip Brown over C-25 Downpour



PC-34 Light Sepia over C-25 Downpour



PC-36 Ironstone over C-25 Downpour



PC-37 Smoked Sienna over C-25 Downpour

Clay: AMACO® A-Mix White Stoneware No. 11

C-25 Layering Notes: Brush on three layers of base coat. Brush on three layers of top coat. (Let dry between coats.)

Firing: Test tiles have been fired to Cone 6


over
C-25
Downpour

www.LayeringAmacoGlazes.com




Join the conversation
www.facebook.com/groups/potterschoiceex



Reorder No. 000000



PC-39 Umber Float over C-25 Downpour




PC-40 True Celadon over C-25 Downpour




PC-42 Seaweed over C-25 Downpour



PC-43 Toasted Sage over C-25 Downpour




PC-44 Sage over C-25 Downpour





PC-46 Lustrous Jade over C-25 Downpour



PC-48 Art Deco Green over C-25 Downpour




PC-49 Frosted Melon over C-25 Downpour




PC-52 Deep Sienna Speckle over C-25 Downpour





PC-55 Chun Plum over C-25 Downpour




PC-56 Ancient Copper over C-25 Downpour



PC-57 Smokey Merlot over C-25 Downpour



PC-59 Deep Firebrick over C-25 Downpour



PC-64 Aventurine over C-25 Downpour



The Art & Creative Materials Institute AP (Approved Product) seal certifies this product to be safe for use by all ages. Conforms to ASTM D-4236.



The Art & Creative Materials Institute CL (Caution Label) seal restricts this product from children under the age of 13. Older users must follow all cautionary labeling. Conforms to ASTM D-4236.

Color may vary between printed copies.