

LAYERING Potter's Choice

Celadon

Cone 5/6



PC-4 Palladium over C-55 Poppy




PC-12 Blue Midnight over C-55 Poppy




PC-20 Blue Rutile over C-55 Poppy



PC-21 Arctic Blue over C-55 Poppy



PC-23 Indigo Float over C-55 Poppy



PC-28 Frosted Turquoise over C-55 Poppy



PC-29 Deep Olive Speckle over C-55 Poppy



PC-31 Oatmeal over C-55 Poppy



Conforms to
ASTM D-4236



PC-32 Albany Slip Brown over C-55 Poppy



PC-34 Light Sepia over C-55 Poppy



PC-35 Oil Spot over C-55 Poppy

Clay: AMACO® A-Mix White Stoneware No. 11

C-55 Layering Notes: Brush on three layers of base coat. Brush on three layers of top coat. (Let dry between coats.)

Firing: Test tiles have been fired to Cone 6

over
C-55
Poppy

www.LayeringAmacoGlazes.com




f Join the conversation
www.facebook.com/groups/potterschoiceex

Reorder No. 11627E



PC-40 True Celadon over C-55 Poppy



PC-41 Vert Lustre over C-55 Poppy



PC-42 Seaweed over C-55 Poppy



PC-43 Toasted Sage over C-55 Poppy



PC-45 Dark Green over C-55 Poppy



PC-46 Lustrous Jade over C-55 Poppy



PC-48 Art Deco Green over C-55 Poppy



PC-49 Frosted Melon over C-55 Poppy




PC-53 Ancient Jasper over C-55 Poppy



PC-55 Chun Plum over C-55 Poppy



PC-57 Smokey Merlot over C-55 Poppy



PC-59 Deep Firebrick over C-55 Poppy



PC-63 Cosmic Tea Dust over C-55 Poppy



PC-64 Aventurine over C-55 Poppy



The Art & Creative Materials Institute AP (Approved Product) seal certifies this product to be safe for use by all ages. Conforms to ASTM D-4236.



The Art & Creative Materials Institute CL (Caution Label) seal restricts this product from children under the age of 13. Older users must follow all cautionary labeling. Conforms to ASTM D-4236.

Color may vary between printed copies.